DID YOU KNOW?

about our...





Grade 80 Swivel Safety Hook

Safety hook locks while swivel action assists with aligning the load prior to lifting.

SWIVEL SAFETY HOOK POWDER COAT / HEC / GRADE 80

	Part	Qfind	Size	WLL	BL	
			M	(tonne)	(tonne)	
	ULHK08PSS-06	HSS6	6	1.12	4.48	
	ULHK08PSS-08	HSS8	8	2.00	8.00	
	ULHK08PSS-10	HSS10	10	3.15	12.60	
	ULHK08PSS-13	HSS13	13	5.30	21.20	
	ULHK08PSS-16	HSS16	16	8.00	32.00	

APPLICATIONS

- Use with Grade 80 lifting components
- · Lifting with chains and synthetic slings

FEATURES

- Conforms to AS 3776
- 100% magnaflux crack detection
- 360° swivel motion
- Safety hook prevents components from releasing when being lifted





MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

